

The Cinema Series of LED LiteRibbon is the single best applied phosphor LED product available in the industry. With staggering CRI and full-spectrum output, the Cinema Series is 30% brighter than the previous VHO Pro LiteRibbon. This all-new LiteRibbon proudly joins the LiteGear Cinema family of unified color-space products including S2 LiteMat, LiteMat Plus, and LiteTile Plus.



## 12 SPECIFICATIONS, 12V DC

<b>Product Name:</b> LiteRibbon Cinema Daylite, X5 12V DC, 1 m
<b>Item Number:</b> LR-CS-12-HY-DAY-X5
<b>Optical System:</b> Flexible LED tape
<b>Color Name:</b> Cinema Daylite
<b>Power:</b> 100W (total potential power per roll)
<b>Voltage Input:</b> 12V DC nominal (8-13.5V DC constant voltage)
<b>Current:</b> 8.33A (total potential current per 1 meter roll)
<b>CCT:</b> 6000K (+/-100K)
<b>CRI:</b> 95
<b>TLCI:</b> 98
<b>Beam Angle:</b> 120°
<b>Lumens (lm) Whites:</b> 9475.6
<b>Weight:</b> .09 kg. (3.1 oz.) (with input lead)
<b>Width:</b> 41.65 mm (0.47 in.)
<b>Length:</b> 1 m (39 in.)
<b>Ribbon Overall Thickness:</b> 1.5 mm (0.06 in.)
<b>Cut Segment Length:</b> 50 mm (1.96 in.)
<b>Cut Segments per Meter:</b> 20
<b>Total LED Quantity:</b> 600
<b>LEDs per Meter:</b> 600
<b>LEDs per Cut Segment:</b> 30
<b>LED Spacing:</b> 8.3 mm (0.33 in.)
<b>Dimming Range:</b> 0-100%
<b>Operating Temperature:</b> -20°C to +50°C (68°F to +122°F)
<b>Connector:</b> Phoenix 3-Female
<b>Mounting:</b> PSA backing
<b>LED Lifetime:</b> 50,000 Hrs
<b>IP Rating:</b> 20
<b>Certifications:</b> UL Listed (Canada/US), CE Compliant (Europe)

## 24 SPECIFICATIONS, 24V DC

<b>Product Name:</b> LiteRibbon Cinema Daylite, X5 24V DC, 2 m
<b>Item Number:</b> LR-CS-24-DAY-HD-X5
<b>Optical System:</b> Flexible LED tape
<b>Color Name:</b> Cinema Daylite
<b>Power:</b> 200W (total potential power per roll)
<b>Voltage Input:</b> 24V DC nominal (16-26V DC constant voltage)
<b>Current:</b> 8.33A (total potential current per 1 meter roll)
<b>CCT:</b> 6000K (+/-100K)
<b>CRI:</b> 95
<b>TLCI:</b> 98
<b>Beam Angle:</b> 120°
<b>Lumens (lm) Whites:</b> 9849.8
<b>Weight:</b> .09 kg. (3.1 oz.) (with input lead)
<b>Width:</b> 41.65 mm (0.47 in.)
<b>Length:</b> 2 m (78 in)
<b>Ribbon Overall Thickness:</b> 1.5 mm (0.06 in.)
<b>Cut Segment Length:</b> 100 mm (3.94 in.)
<b>Cut Segments per Meter:</b> 20
<b>Total LED Quantity:</b> 1200
<b>LEDs per Meter:</b> 600
<b>LEDs per Cut Segment:</b> 60
<b>LED Spacing:</b> 8.3 mm (0.33 in.)
<b>Dimming Range:</b> 0-100%
<b>Operating Temperature:</b> -20°C to +50°C (68°F to +122°F)
<b>Connector:</b> Phoenix 3-Female
<b>Mounting:</b> PSA backing
<b>LED Lifetime:</b> 50,000 Hrs
<b>IP Rating:</b> 20
<b>Certifications:</b> UL Listed (Canada/US), CE Compliant (Europe)

## PHOTOMETRIC DATA 12V

	12 in. FC (spread, in.)	30 cm. Lux (spread, cm.)	24 in. FC (spread, in.)	61 cm Lux (spread, cm.)	36 in. FC (spread, in.)	91 cm. Lux (spread, cm.)	48 in. FC (spread, in.)	122 cm Lux (spread, cm.)	60 in. FC (spread, in.)	152 cm. Lux (spread, cm.)
6000K, 12V	1048 (38.4x29.6)	11281 (98x75)	262 (76.8x59.3)	2820 (195x151)	116.4 (115.2x88.9)	1253 (293x226)	65.5 (153.6x118.6)	705 (390x301)	41.9 (192x148.2)	451 (488x376)

## PHOTOMETRIC DATA 24V

	12 in. FC (spread, in.)	30 cm. Lux (spread, cm.)	24 in. FC (spread, in.)	61 cm Lux (spread, cm.)	36 in. FC (spread, in.)	91 cm. Lux (spread, cm.)	48 in. FC (spread, in.)	122 cm Lux (spread, cm.)	60 in. FC (spread, in.)	152 cm. Lux (spread, cm.)
6000K, 24V	1401.6 (37x27.6)	15087 (94x70)	350.4 (73.9x55.2)	3772 (188x140)	155.7 (110.9x82.8)	1676 (282x210)	87.6 (147.8x110.4)	943 (375x281)	56.1 (184.8x138)	603 (469x351)

## ACCESSORIES

### Control

LD-PRO-HYBRID LiteDimmer Hybrid 8A

LD-PRO-HYBRID-HICAP LiteDimmer Hybrid 16A

### Power Supply

PS-12V-8A-F-UL Power Supply, Desktop, 12V DC, 8A, 96W

PS-12V-16A-PH Power Supply, Desktop, 12V DC, 16A, 240W

### Cable Extension

CA-PH3-EXT-12F-FLAT-B Phoenix-3 Extension Cable, 12 ft.

## DAYLITE — SPECTRAL DISTRIBUTION

