



The Cinema Series of LED LiteRibbon is the single best applied phosphor LED product available in the industry. With staggering CRI and full-spectrum output, the Cinema Series is 30% brighter than the previous VHO Pro LiteRibbon. This all-new LiteRibbon proudly joins the LiteGear Cinema family of unified color-space products including S2 LiteMat, LiteMat Plus, and LiteTile Plus.



12 SPECIFICATIONS, 12V DC

Product Name: LiteRibbon Cinema Daylite, X3 12V DC, 1.5 m
Item Number: LR-CS-12-DAY-HD-X3
Optical System: Flexible LED tape
Color Name: Cinema Daylite
Power: 90W (total potential power per 1.5 meter roll)
Voltage Input: 12V DC nominal (8-13.5V DC constant voltage)
Current: 7.5A (total potential current per 1.5 meter roll)
CCT: 6000K (+/-100K)
CRI: 95
TLCI: 98
Beam Angle: 120°
Lumens (lm) Whites: 5899.6
Weight: .08 kg. (2.75 oz.) (with input lead)
Width: 25 mm (0.99 in.)
Length: 1.5 m (4.9 ft)
Ribbon Overall Thickness: 1.5 mm (0.06 in.)
Cut Segment Length: 50 mm (1.96 in.)
Cut Segments per Meter: 20
Total LED Quantity: 540
LEDs per Meter: 360
LEDs per Cut Segment: 18
LED Spacing: 8.3 mm (0.33 in.)
Dimming Range: 0-100%
Operating Temperature: -20°C to +50°C (68°F to +122°F)
Connector: Phoenix 3-Female
Mounting: PSA backing
LED Lifetime: 50,000 Hrs
IP Rating: 20
Certifications: UL Listed (Canada/US), CE Compliant (Europe)

24 SPECIFICATIONS, 24V DC

Product Name: LiteRibbon Cinema Daylite, X3 24V DC, 3 m
Item Number: LR-CS-24-DAY-HD-X3
Optical System: Flexible LED tape
Color Name: Cinema Daylite
Power: 180W (total potential power per 3 meter roll)
Voltage Input: 24V DC nominal (16-26V DC constant voltage)
Current: 7.5A (total potential current per 3 meter roll)
CCT: 6000K (+/-100K)
CRI: 95
TLCI: 98
Beam Angle: 120°
Lumens (lm) Whites: 5572.5
Weight: .08 kg. (2.75 oz.) (with input lead)
Width: 25 mm (0.99 in.)
Length: 3 m (9.9 ft)
Ribbon Overall Thickness: 1.5 mm (0.06 in.)
Cut Segment Length: 100 mm (1.96 in.)
Cut Segments per Meter: 10
Total LED Quantity: 1080
LEDs per Meter: 360
LEDs per Cut Segment: 36
LED Spacing: 8.3 mm (0.33 in.)
Dimming Range: 0-100%
Operating Temperature: -20°C to +50°C (68°F to +122°F)
Connector: Phoenix 3-Female
Mounting: PSA backing
LED Lifetime: 50,000 Hrs
IP Rating: 20
Certifications: UL Listed (Canada/US), CE Compliant (Europe)

PHOTOMETRIC DATA 12V

	12 in. FC (spread, in.)	30 cm. Lux (spread, cm.)	24 in. FC (spread, in.)	61 cm Lux (spread, cm.)	36 in. FC (spread, in.)	91 cm. Lux (spread, cm.)	48 in. FC (spread, in.)	122 cm Lux (spread, cm.)	60 in. FC (spread, in.)	152 cm. Lux (spread, cm.)
6000K, 12V	707.2 (38.4x26.7)	7612 (98x68)	176.8 (76.8x53.3)	1903 (195x135)	78.6 (115.2x80)	846 (293x203)	44.2 (153.6x106.6)	476 (390x271)	28.3 (192x133.3)	304 (488x339)

PHOTOMETRIC DATA 24V

	12 in. FC (spread, in.)	30 cm. Lux (spread, cm.)	24 in. FC (spread, in.)	61 cm Lux (spread, cm.)	36 in. FC (spread, in.)	91 cm. Lux (spread, cm.)	48 in. FC (spread, in.)	122 cm Lux (spread, cm.)	60 in. FC (spread, in.)	152 cm. Lux (spread, cm.)
6000K, 24V	873.6 (39.9x28.6)	9403 (101x73)	218.4 (79.9x57.2)	2351 (203x145)	97.1 (119.8x85.8)	1045 (304x218)	54.6 (159.8x114.4)	588 (406x291)	34.9 (199.7x143)	376 (507x363)

ACCESSORIES

Control

LD-PRO-HYBRID LiteDimmer Hybrid 8A

LD-PRO-HYBRID-HICAP LiteDimmer Hybrid 16A

Power Supply


PS-12V-8A-F-UL Power Supply, Desktop, 12V DC, 8A, 96W

PS-12V-16A-PH Power Supply, Desktop, 12V DC, 16A, 240W



Cable Extension

CA-PH3-EXT-12F-FLAT-B Phoenix-3 Extension Cable, 12 ft.


DAYLITE — SPECTRAL DISTRIBUTION



8.3 mm (0.33 in.)



12 24 1.5 mm (.06 in.)



LITEGEAR, INC. 4406 Vanowen St, Burbank, CA 91505, USA

Hours: Monday-Friday 8AM-4:30PM (PST)

Tel: +1 818 358-8542 SMS: +1 818 495 0600

Email: info@litegear.com or support@litegear.com Web: www.litegear.com

