This all-in-one platform can be powered by either 110/240VAC and 12/24VDC sources, offering unmatched versatility for a wide range of applications. It features easily adjustable ball joint mounts, allowing you to direct light precisely where it's needed. Its directional lighting and low-profile design reduce dangerous glare that can distract motorists and workers. Additionally, the exceptionally long-life LEDs ensure up to 50,000 hours of operation.

SPECIFICATIONS

Product Name: SiteLite Item Number: 0320 Model: Gen3 Beam Angle: 120° AC Input Voltage: 100-270VAC~ 60HZ AC Input Current: 0.7A AC Power Rating: 75 W; 0.98PF DC Input Voltage: 12/24VDC == DC Input Current: 6A-- @ 12VDC--3A-- @ 24VDC--DC Power Rating: 64W @ 12VDC---67.2W @ 24VDC ---Color Temperature: 4,000K Estimated LED Lifetime: 50,000 Hours Power Connector: Ecomate PL7 IP Rating: IP65 Max Operating Temp: 50°F (122°C) Weight: 7 lbs (3.17 kg) Total LED Quantity: 216 Dimensions: Height: 31.3 in. (796 mm) Width: 4.97 in. (126.2 mm) Depth: 2.65 in. (67.3 mm)



Mounting: 1 1/8 Pin
Certifications: Pending

	ССТ	Luminous Flux	3.3 ft, FC (ft)	1 m, Lux (m)	9.8 ft, FC (ft)	3 m, Lux (m)
	4,000K	11,740 lm	360	3,934	61	436


ACCESSORIES


Black Aluminum BaseLite Stand

RECOMMENDED ACCESSORY

Instagrid Go Portable Battery Power Supply









litegear.com/sitelite





• Portable

- Rapid Deployment
- Omni-Directional
- IP 65 Rated
- AC (100-240V) or DC (12-24V) Powered

environments This easy to setup AC/DC system features high-output, low power LEDs with a low-

- High Output
- Low Power Draw (150W)
- Neutral White Light (4300K)

profile omni-directional design.

- Long Life LEDs (50,000 hours)
- Insect Neutral Emitters

